

In the Claims:

1. (Canceled)

2. (Currently amended) ~~The A display panel module according to claim 1,~~

comprising:

a display panel defining a screen on a front surface;

an electrically conducting frame enclosing the display panel; and

an electrically conductive member located behind the display panel and

electrically connected to the electrically conductive frame, wherein

A¹ a loop line is established through the electrically conductive member and the electrically conductive frame, said loop line having a length different from a wavelength of a driving signal supplied to the display panel.

3. (Original) The display panel module according to claim 2, wherein said length of the loop line is set smaller than a half of the wavelength of the driving signal.

4. (Original) The display panel module according to claim 3, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than a quarter of the wavelength of

the driving signal.

5. (Original) The display panel module according to claim 2, wherein said length of the loop line is set smaller than a quarter of the wavelength of the driving signal.

Cont'd
A1
6. (Original) The display panel module according to claim 5, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than one eighth of the wavelength of the driving signal.

7. (Currently amended) A display panel module comprising:
a display panel defining a screen on a front surface;
a panel-shaped module component superposed on a rear surface of the display panel; and
an electrically insulating ~~frame~~ bezel enclosing the display panel and the panel-shaped module component so as to couple the module component to the display panel.

8. (Canceled)

9. (Currently amended) The electronic apparatus according to claim-8 10, wherein said display panel, said module component and said electrically conductive frame form a display panel module.

10. (Currently amended) The An electronic apparatus according to claim-9, comprising:

a display panel defining a screen on a front surface;

a panel-shaped module component superposed on a rear surface of the display panel;

an electrically conductive frame enclosing the display panel and the panel-shaped module component so as to couple the module component to the display panel; and

an electrically conductive member located behind the display panel and electrically connected to the electrically conductive frame wherein

a loop line is established through the electrically conductive member and the electrically conductive frame, said loop line having a length different from a wavelength of a driving signal supplied to the display panel.

11. (Original) The electronic apparatus according to claim 10, wherein said length of the loop line is set smaller than a half of the wavelength of the driving signal.

12. (Original) The electronic apparatus according to claim 11, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than a quarter of the wavelength of the driving signal.

Control

A1

13. (Original) The electronic apparatus according to claim 10, wherein said length of the loop line is set smaller than a quarter of the wavelength of the driving signal.

14. (Original) The electronic apparatus according to claim 13, wherein electric joints are established between the electrically conductive member and the electrically conductive frame at positions spaced by intervals smaller than one eighth of the wavelength of the driving signal.

15. (New) The display panel module according to claim 7, wherein said module component comprises at least one of a diffuser, a prism plate, a light pipe, a light source and a reflector.
